

■ Metal Composite (一般用)

①一般線

P/N	寸法 (mm)	Inductance範囲 (μ H)																				
		0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1	2	4	6	8	10	20	30	40	60	80	100
SMF0310-AH	3.4 x 3.4 x H1.0max				0.47	4.7																
SMF0312-AH	3.4 x 3.4 x H1.2max				0.47	4.7																
SMF0315-AH	3.4 x 3.4 x H1.5max				0.47	4.7																
SMF0320-AH	3.4 x 3.4 x H2.0max				0.47	4.7																
TSPI-0412	4.2 x 4.4 x H1.2max			0.33	4.7																	
TSPI-0402	4.2 x 4.4 x H2.0max	0.10														10						
TSPI-0518	5.2 x 5.4 x H2.0max				0.47	4.7											10					
TSPI-0503	5.2 x 5.4 x H3.0max	0.2														4.7						
TMPA606010SP	6.1 x 6.1 x H1.0max														6.8	10						
TSPI-061H	6.6 x 7.1 x H2.0max	0.10														6.8						
TSPI-0618	6.6 x 7.1 x H2.0max	0.10													4.7							
TSPI-0624	6.6 x 7.1 x H2.4max	0.10															10					

P/N	寸法 (mm)	Inductance範囲 (μ H)																				
		0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1	2	4	6	8	10	20	30	40	60	80	100
TSPI-0603	6.6 x 7.1 x H3.0max	0.10															10					
TSPI-063T	6.6 x 7.1 x H3.0max			0.33														22				
TSPC0603H	6.6 x 7.1 x H3.0max			0.22														22				
TSPA0603S	6.6 x 7.1 x H3.0max	0.15																22				
TSPI-0604	6.6 x 7.1 x H4.0max										1.0								68			
TMPA0604S	6.6 x 7.1 x H4.0max	0.15										1.0										
TMPA0605S	6.6 x 7.1 x H5.0max					0.47													47			
TMPC0605H	6.6 x 7.3 x H5.0max					0.33														68		
ESPC-0804	8.0 x 8.5 x H4.0max				0.22														33			
TMPC1002H	10.0 x 11.0 x H2.0max										1.0						8.2					
TSPI-1034	10.0 x 11.0 x H3.4max				0.22												2.2					
TMPC1004H	10.0 x 11.0 x H4.0max	0.15																		68		
TSPI-1040	10.0 x 11.0 x H4.0max	0.19													3.3							

